

TECHNICAL CHARACTERISTICS

wineo 800				wineo	
Covering type according to EN ISO 10582: Heterogeneous resilient-flooring for glueless installation					
	wineo 800 wood	wineo 800 wood XL	wineo 800 stone XL		
Format	1212 x 185 mm	1505 x 237 mm	914 x 480 mm		
Product thickness	5 mm	5 mm	5 mm		
Planks, tiles / m ² per box	8 / 1.79 m ²	6 / 2.14 m ²	6 / 2.63 m ²		
Boxes / m ² per pallet	64 / 114.75 m ²	56 / 119.84 m ²	44 / 115.72 m ²		
Guarantee	25 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de				
Classification				Product composition	
	Utilization class 23 Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices		1	Surface sealing
	Utilization class 33 Heavy-duty use in the commercial sector EN ISO 10874	Department stores, lobby's, schools, open plan offices, corridors		2	Surface texture Various embossings
	Utilization class 42 Normal use in the light industrial sector EN ISO 10874	Storage rooms, workshops		3	Wear layer Thickness 0.55 mm
	Wear layer binder content EN ISO 10582	Type I		4	Decor Decor film
	Wear resistance EN 660-2	Group T acc. to DIN EN 649:2011-05		5	Base layer with glass fibre reinforced
	Reaction to fire EN 13501-1	B _{fl} - s1		6	Profile connection Connect Technology
	Anti slip category DIN 51130	R 9		7	Backing
	Slip resistance EN 13893	$\mu \geq 0.30 - DS$			Insulation mat silentCOMFORT (separately available)
	Anti-static properties EN 1815	≤ 2 kV			stone - real joint technology selected decors
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time		Certifications	
	Light fastness EN ISO 105-B02	≥ 6		<p>windmüller flooring products WFP GmbH Nord-West-Ring 21 D-32852 Augustdorf</p> <p>- 09 - Elastischer Bodenbelag DIN 25110/2 EN 14041:2004</p> <p> Resilient Flooring to be used within a building.</p> <p>EMISSIONS DANS L'AIR INTÉRIEUR A+</p> <p>Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (faibles émissions) à A+ (très faibles émissions)</p> <p></p> <p> factory made coated</p>	
	Residual indentation EN ISO 24343-1	~ 0.07 mm			
	Castor chair test EN 425 / ISO 4918	Type W – no visible change			
	Thermal resistance EN 12667	~ 0.033 (m ² K)/W ~ 0.0254 (m ² K)/W in combination with silentCOMFORT			
	Impact sound reduction EN ISO 16251-1	~ 7 dB up to 14 dB in combination with silentCOMFORT			
	Dimension stability EN ISO 23999	~ 0.1 %			
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203			

Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.