

## base FR

Product data sheet no. 9164 - R - 05

Issue: February 2022

Like the SPORTEC® base MS, the **SPORTEC® base FR** also protects the substrate from impacts of heavy weights, but additionally has increased fire protection values. Furthermore, it equally features excellent sound insulation properties.

### Material

Material:

A mixture of chosen EPDM rubber granules bonded with polyurethane elastomer

### Product design

Colour(s): black  
(low colour differences are conditional of material)

Colour(s):



base FR

Surface: open-pored smooth  
Lower side: dimpled base, with reinforcement mesh (at 30mm)  
flat base, without mesh (at 20 mm)

### Dimensions / Tolerances / Weight

Thickness(es): 30 mm (± 2 mm)  
20 mm (± 2 mm) (only possible at 1000 mm x 1000 mm) - no connector pins

The product data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on [www.kraiburg-relastec.com/sportec](http://www.kraiburg-relastec.com/sportec)

page 1 of 3

## base FR

Product data sheet no. 9164 - R - 05

Issue: February 2022

Length x width:	500 mm / 500 mm (± 0.8 %) 500 mm / 1000 mm (± 0.8 %) 1000 mm / 1000 mm (± 0.8 %)
Area weight:	approx. 27.0 kg/m <sup>2</sup> approx. 18.4 kg/m <sup>3</sup>
Weight slab:	approx. 6.8 kg (at 500 mm x 500 mm) approx. 13.5 kg (at 1000 mm x 500 mm) approx. 27.0 kg (at 1000 mm x 1000 mm) approx. 18.4 kg (at 20 mm x 1000 mm x 1000 mm)

## Product Testing

Fire resistance:	C <sub>fl</sub> -s1 (DIN EN 13501-1)
Tensile strength:	min. 0.75 N/mm <sup>2</sup> (EN ISO 1798)
Elongation at break:	min. 50 % (EN ISO 1798)
Hardness:	60 ± 5 Shore A (DIN 53505)
Temperature range:	-30°C to 80°C (internal tested)
Force reduction:	approx. 51 % (at 30 mm) (internal tested) approx. 35 % (at 20 mm) (internal tested)
Step sound insulation:	25 dB (DIN EN ISO 10140-3:2015-11) 30 dB (with SPORTEC team cup 10 mm) (DIN EN ISO 10140-3:2015-11) 33 dB (with SPORTEC supercell DC2 10 mm) (DIN EN ISO 10140-3:2015-11)
VOC emission rating:	



The product data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on [www.kraiburg-relastec.com/sportec](http://www.kraiburg-relastec.com/sportec)

page 2 of 3

## Installation

Installation has to be done in accordance to the Installation Recommendation of **SPORTEC® base FR**.

The product data sheet is not subject to any change service! All information is without guarantee.

Latest version of this document available on [www.kraiburg-relastec.com/sportec](http://www.kraiburg-relastec.com/sportec)

page 3 of 3